

Symmetrical Horn Carrier Class Gen 2

HORN ANTENNA WITH N-FEMALE CONNECTORS

Symmetrical Horn CC Antennas Gen2 offer unique RF performance in a compact package. Scalar horn antennas have symmetrical main beam with identical beam width in Vertical and Horizontal plane. Exceptionally small side lobes ensure remarkable interference suppression. HG3-CC Gen2 Antennas are ideal for coverage of areas with clients close to the installation site, where null zone issues exist. High density AP clusters and radio co-location is made possible due to unique radiation patterns and compact size.

Symmetrical Horn CC Antennas Gen2 feature multiple improvements of RF performance and design, namely, optically lighter body and significantly improved bracket. Radome is made of more resistant material, and all of HG3-CC Gen2 antennas use only two radome sizes. HG3-CC Gen2 antenna is equipped with N-female connectors.



PRODUCT DIMENSIONS

GAIN

TECHNICAL DATA

Radio Connection	2x N Female Bulkhead Connector						
Antenna Type	Horn						
Materials	UV Resistant polycarbonate, Polypropylene, Aluminium, Zinc, Stainless Steel						
Enviromental	IP55						
Flame Rating	UL 94 HB						
Pole Mounting Diameter	30-80 mm (we recommend as close to 80mm as possible)						
Temperature	-30°C to +55°C (-22°F to +131°F)						
Wind Survival	160 km/hour						
Wind Loading	22 N at 160 km/hour						
Mechanical Tilt	± 25°						
Weight	1.9 Kg / 4.1 lbs – single unit 2.7 Kg / 5.9 lbs – single unit incl. package 27.7 Kg / 61 lbs – carton (10 units)						
Single Unit	Retail Box: 305 × 239 × 183 mm / 12 x 9.4 x 7.2 inch						
10 Units	Carton Box: 940 × 510 × 335 mm / 37 x 20 x 13.2 inch						

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Gain	14.3 dBi
Azimuth/Elevation BW -3 dB	H 33° / V 33°
Azimuth/Elevation BW -6 dB	H 50° / V 50°
Front-to-Back Ratio	33 dB
VSWR Max 5180-5850 MHz	1.6
VSWR Max 5850-6400 MHz	1.9
Beam Efficiency**	92%
Polarization	Dual Linear H + V

Impedance



AZIMUTH PATTERN



ELEVATION PATTERN



1/2 SYMMETRICAL HORN ANTENNAS Rev OCT-2019

RF elements® and Connectorized Symmetrical Horn Antenna are trademarks of RF elements s.r.o., Humenne, Slovakia. All rights of respective trademark owners reserved. © RF elements 2019









V/H Gain (IEEE) V/H VSWR



3D RADIATION DIAGRAM

SCALE: 30dBi COMPATIBLE WITH: ADOBE ACROBAT READER DC. NOT SUPPORTED ON MOBILE. USE MOUSE TO ROTATE THE DIAGRAM. SCROLL IN/OUT TO ZOOM IN/OUT

dBi

										1														
14.2 12	2.7	11.2	9.7	78	.2 (5.7	5.2	3.7	2.2	0.	7 -	0.8	-2.3	-3.	.8 -	5.3	-6.8	-8.3	-9.	8 -	11.3	-12.8	-14.	.3 -15.8

	FRONT	ВАСК	RIGHT	LEFT	UP	DOWN
2/.	SYMMETRICAL HORN ANTENNAS I	Rev OCT-2019	RF elements [®] and Con	nectorized Symmetrical Horn A	ntenna are trademarks of RF ele All rights of respec	ements s.r.o., Humenne, Slovakia. tive trademark owners reserved. © RF elements 2019
W	ww.rfelements.com	Ì				